

# 8. SE-100

## SPECIFICATIONS

Speaker ..... Electret push-pull static type 2-way system  
 Static capacity ..... 140pF (each channel, including the connecting cord)  
 Frequency response ..... 20 to 35,000Hz  
 Sensitivity ..... 95dB or greater (input 100V) with B&K Artificial ear 4153  
 Maximum sound pressure level..... 115dB  
 Distortion ..... Less than 1% (at sound pressure level 100 dB)  
 Separation ..... 40 dB or more (at audible band)  
 Connecting cord ..... 8.2 ft./2.5m (with 4-P plug)  
 Weight ..... 13 oz/360 g (except connecting cord)

**NOTE:**

Specifications and the design subject to possible modification without notice due to improvements.

## PARTS LIST

Key No.	Description	Part No.	
1	Speaker Assembly (Electret type)	SXC-048-0	
2	Case (L)	SXC-041-0	
3	Case (R)	SXC-042-0	
4	Ear Pad	SXC-043-0	
5	4-P Plug with Connecting Cord	K71-643-0	
6	Lead Wire	SXC-044-0	
7	Holder Unit	SXC-045-0	
8	Shaft for Holder	SXC-046-0	
9	Head Band Assembly	SXC-047-0	
10	Capacitor (39pF, DC 2kV)	SCG-001-0	
	Packing Case	H93-641-0	
	Styrol Protector	H92-609-0	
	Operating Guide (SE-100, JB-100)	SRB-009-0	



